



Conference Delegate Unit

Embedded software: hand in hand conference delegate embedded control
software V1.0
TS-0202A



Feature:

- * 48KHZ sampling rate, clear and bright sound, than the CD sound quality, built-in DSP audio processor and no low frequency impact sound.
- * Built-in HIFI speaker, support volume adjustment and howling suppression; when microphone is turned on, the built-in speaker will be automatically turned off.
- * With the 3.5 mm output sockets, for recording or connecting headphones.
- * In voice control mode, the chairman unit and the delegate unit can be turned on by voice control and the voice control sensitivity is adjustable. When the delegate unit is turned on, it will be automatically turned off when the state of no one speaking lasts for 30 seconds, but the chairman is not restricted.
- * With 5-band EQ adjustment function, can adjust sound effects according to the characteristics of different speakers to achieve perfect effect.
- * 100M network transmission, hand in hand cascade, long-distance transmission with good sound quality.
- * The capacitive touch buttons can effectively prevent key knocking noise, creating a good conference environment.

Specifications:

Model	TS-0202A
Microphone type	Cardioid directional Electret
Frequency response	80Hz-16KHz
Input impedance	≥1KΩ
Sensitivity	-46dBV/Pa
Maximum SPL	125dB (THD>3%)
SNR	>80dB (A)
THD	<0.1%
Power consumption	3W
Headphone load	16-32Ω
Maximum headphone volume	40mW
Headphone jack	3.5mm
Standard	IEC60914
Connector	With 1.8m 6-pin aviation connector
Power supply	Controller power supply
Color	Black
Sign in	Touch button sign in
Microphone pole	409mm
Installation	Desktop
Weight	0.86Kg
Size	144×128×62mm