




Voice Evacuation Microphone

VA-6ZRM



Features

- * Support 40 zones, 6 group button paging.
- * Support zone configuration to any grouping.
- * Support consecutive paging for any controller of 1 ~ 6 zones.
- * Support line input / microphone output. And output volume is adjustable.
- * Remote microphone paging priority can be configured.
- * Display the zone status of the associated controller in real time.
- * Support 24 DC power supply, POE power supply.
- * The system supports up to 28 remote microphones.

Specifications

Analog audio

MIC microphone input	
Sensitivity	10MV±1mV
Frequency response	200Hz~10kHz
Input impedance	≥1kΩ
LINE unbalanced line audio input	
Sensitivity	775MV±50mV
Frequency response	80Hz~16kHz
Impedance	≥10kΩ

Balanced line output

Amplitude	1000MV±50mV
Distortion	<0.3%, 1 kHz
Frequency response	200Hz~10kHz
Output impedance	470Ω
SNR	>60dB

Communication

CAN interface	Remote MIC console CAN interface
	Baud rate 100Kbps
	Support up to 32 remote MIC consoles

Mechanical indicators

Dimension(mm)	197 x 115 x 44 mm
Net weight	About 1.2KG
Installation	Desktop or 19-inch cabinet
Color	Black

Environmental requirements

Operating temperature	+5℃ ~ +40℃
Storage temperature	-20℃ ~ +70℃
Relative temperature	<95%